

0001 0001 0001

2



# Naval Research Laboratory

Washington, DC 20375-5000

NRL Memorandum Report 6390

AD-A212 572

## Radio Frequency Linac Driven Free-Electron Laser Configurations

C.M. TANG, P. SPRANGLE, A. TING AND B. HAFIZI\*

*Beam Physics Branch  
Plasma Physics Division*

*\*Science Applications Intl. Corp.  
McLean, VA*

September 7, 1989



Approved for public release; distribution unlimited.

89 9 18 195

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE			Approved for public release; distribution unlimited.		
4. PERFORMING ORGANIZATION REPORT NUMBER(S)  NRL Memorandum Report 6390			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION  Naval Research Laboratory		6b. OFFICE SYMBOL (If applicable)  Code 4790	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code)  Washington, DC 20375-5000			7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION  Office of Naval Research		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)  Arlington, VA 22217			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
			WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification)  Radio Frequency Linac Driven Free-Electron Laser Configurations					
12. PERSONAL AUTHOR(S)  Tang, C.M., Sprangle, P., Ting, A. and Hafizi, * B.					
13a. TYPE OF REPORT  Interim		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) 1989 September 7	
15. PAGE COUNT 34					
16. SUPPLEMENTARY NOTATION *Science Application Intl. Corp., McLean, VA					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	FEL SSPA		
			MOPA		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>Recent developments in accelerator technology and the optical guiding property of the free electron laser (FEL) radiation indicate that the RF linacs may be a strong contender for driving high average power FEL amplifiers. We discuss two RF linac driven FEL configurations: the master oscillator power amplifier (MOPA) and the single stage power amplifier (SSPA). Our numerical results are obtained using the source dependent expansion (SDE) method in the computer code SHERA. The SDE method and the code SHERA are discussed and illustrations of the MOPA and SSPA configurations presented.</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL C.M. Tang			22b. TELEPHONE (Include Area Code) (202) 7674148		22c. OFFICE SYMBOL Code 4790

## CONTENTS

INTRODUCTION .....	1
THE FORMULATION OF 3 D FEL EQUATIONS .....	2
DESCRIPTION OF THE 3-D FEL CODE SHERA .....	5
RF LINAC DRIVEN POWER AMPLIFIERS .....	7
I. Master Oscillator Power Amplifier (MOPA) .....	7
II. Single Stage Power Amplifier (SSPA) .....	9
CONCLUSIONS .....	10
ACKNOWLEDGMENTS .....	10
REFERENCES .....	11
DISTRIBUTION LIST .....	23

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Avail. and/or	
Dist. Applied	
A-1	

# **RADIO FREQUENCY LINAC DRIVEN FREE-ELECTRON LASER CONFIGURATIONS**

## **Introduction**

Significant advances in radio frequency (RF) linac technology concerning the reduction of emittance and increase in beam current have been taking place. Lower emittance allows for a smaller electron beam radius and thus higher current densities and laser gain. Under appropriate conditions, the radiation generated in a free electron laser (FEL) can be focused and overcome the natural tendency to diffract (spread transversely). This optical guiding phenomenon was first analyzed in the low gain regime<sup>1</sup>, and later in the exponential gain regime<sup>2-7</sup>. Optical guiding in the FEL can enhance the gain and efficiency and is an integral part of the configurations illustrated in this paper.

We have presented a formalism for describing the three-dimensional radiation field in FELs called the source dependent expansion (SDE) method<sup>6-7</sup>. In this approach, the radiation field is decomposed into a sum of complete normal modes. Instead of using the usual modal expansion consisting of vacuum Gaussian Laguerre functions, the SDE method incorporates the source function (driving current) self-consistently into the functional dependence of, i) the radiation waist, ii) the radiation wavefront curvature and iii) the complex radiation amplitude. The SDE method significantly reduces the number of modes that are required to model the radiation field and reduces the computational time and cost of the simulations.

In our numerical examples the electron dynamics include: i) betatron oscillations, ii) finite emittance and iii) energy spread. The FEL equations together with the SDE method

are implemented in the computer code SHERA. The code is applied to the analysis of high extraction FELs driven by RF linacs. Two FEL configurations, which we considered, are the i) master oscillator power amplifier (MOPA) and ii) single stage power amplifier (SSPA). The schematic configurations are shown in Fig. 1. In both of those configurations, optical guiding plays a central role.

### The Formulation of 3-D FEL Equations

We will consider a realistic, linearly polarized wiggler expressed in terms of the vector potential,

$$\mathbf{A}_w(x, y, z) = A_x(x, y, z) \cos\left(\int_0^z k_w(z') dz'\right) \hat{e}_x, \quad (1)$$

where  $A_x(x, y, z)$  and  $k_w(z)$  are slowly varying functions of  $z$ . The expressions for  $A_x(x, y, z)$  takes on different forms depending on the shape of the magnetic pole face.

The linearly polarized radiation field is

$$\mathbf{A}_R(r, \theta, z, t) = -A(r, \theta, z) \exp[i\omega(z/c - t)] \hat{e}_x/2 + \text{c.c.}, \quad (2)$$

where  $A(r, \theta, z) = |A(r, \theta, z)| e^{i\phi(r, \theta, z)}$  is the complex amplitude of the radiation field expressed in polar variables,  $\omega$  is the frequency, and c.c. denotes the complex conjugate.

The wave equation governing  $\mathbf{A}_R$  is

$$\left( \frac{1}{r} \frac{\partial}{\partial r} r \frac{\partial}{\partial r} + \frac{1}{r^2} \frac{\partial^2}{\partial \theta^2} + \frac{\partial^2}{\partial z^2} - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \right) \mathbf{A}_R = -\frac{4\pi}{c} J_x \hat{e}_x, \quad (3)$$

where  $J_x$  is the driving current density. The detailed representation for the current is given in Ref. 8. Using the SDE method<sup>6-7</sup>, the radiation field is represented in the form,

$$A(r, \theta, z) = \sum_{m,p} C_{m,p}(\theta, z) D_m^p(r, z), \quad (4a)$$

where

$$\frac{|e|}{\sqrt{2}m_0c^2} C_m^p(\theta, z) = a_{m,p}(z) \cos(p\theta) + b_{m,p}(z) \sin(p\theta), \quad (4b)$$

$$D_m^p(\xi) = \frac{2}{r_s(z)} \left( \frac{m!}{(m+p)!} \right)^{1/2} \xi^{p/2} L_m^p(\xi) \exp[-(1 - i\alpha(z))\xi/2], \quad (4c)$$

$$\xi = \frac{2r^2}{r_s^2(z)}, \quad (4d)$$

and

$$\int_0^\infty D_m^p(\xi) [D_n^p(\xi)]^* r dr = \delta_{m,p}. \quad (4e)$$

The functional dependence of the spot size  $r_s$  and curvature  $\alpha$  are governed by the driving current.

Multiplying both sides of Eq. (3) by  $\exp[i(\omega(z/c - t))]$  and integrating over  $t$ , from 0 to  $2\pi/\omega$ , then multiplying both sides by  $D_m^p \cos(p\theta)$  or  $D_m^p \sin(p\theta)$  and integrating over  $r$ , from 0 to  $\infty$ , yields the following SDE equations governing the radiation field,

$$\begin{aligned} \left[ \frac{\partial}{\partial z} + Q_{m,p}(z) \right] \begin{bmatrix} a_{m,p}(z) \\ b_{m,p}(z) \end{bmatrix} - i\sqrt{m(m+p)}B(z) \begin{bmatrix} a_{m-1,p}(z) \\ b_{m-1,p}(z) \end{bmatrix} \\ - i\sqrt{(m+1)(m+p+1)}B^*(z) \begin{bmatrix} a_{m+1,p}(z) \\ b_{m+1,p}(z) \end{bmatrix} = -i \begin{bmatrix} F_{m,p}(z) \\ G_{m,p}(z) \end{bmatrix}, \end{aligned} \quad (5)$$

where

$$Q_{m,p}(z) = \frac{r'_s}{r_s} + i(2m+p+1) \left[ \frac{c}{\omega} \frac{(1+\alpha^2)}{r_s^2} - \alpha \frac{r'_s}{r_s} + \frac{\alpha'}{2} \right], \quad (6)$$

$$B(z) = - \left[ \alpha \frac{r'_s}{r_s} + \frac{c}{\omega} \frac{(1-\alpha^2)}{r_s^2} - \frac{\alpha'}{2} \right] - i \left[ \frac{r'_s}{r_s} - 2 \frac{c}{\omega} \frac{\alpha}{r_s^2} \right], \quad (7)$$

$$\begin{bmatrix} F_{m,p} \\ G_{m,p} \end{bmatrix} = \kappa \left( \frac{1}{1+\delta_{p,0}} \right) \left\langle \frac{a_w(\tilde{x}, \tilde{y}, z) [\tilde{D}_m^p]^* e^{-i(\psi-\tilde{\phi})}}{\tilde{\gamma}\tilde{\beta}_z} \begin{bmatrix} \cos p\tilde{\theta} \\ \sin p\tilde{\theta} \end{bmatrix} \right\rangle, \quad (8)$$

where  $\kappa = (1/2)(\omega_b^2/c^2)(c/\omega)F_B\sigma_b$ , “ $\sim$ ” on top of a quantity denotes the instantaneous values of the variable of a given particle at the axial position  $z$ , \* denotes the complex conjugate and the prime denotes a derivative with respect to  $z$ , i.e.,  $' = \partial/\partial z$ . In addition,  $a_w = (|e|/\sqrt{2}m_0c^2)A_z$  is the normalized wiggler amplitude,  $F_B = J_0(b) - J_1(b)$  for a linearly polarized wiggler,  $b = a_w(0,0,z)^2/2(1+a_w(0,0,z)^2)$ ,  $\sigma_b$  is the effective area associated with the transverse electron beam profile,  $\omega_b = (4\pi|e|^2n_0/m_0c^2)^{1/2}$  is the plasma frequency of

the electron beam on axis,  $\delta_{p,0} = 1$  for  $p = 0$ , and  $\delta_{p,0} = 0$ , otherwise. The symbol  $\langle \rangle$  denotes the average

$$\langle (\dots) \rangle = \int_0^{2\pi} \frac{d\psi_0}{2\pi} \int dx_0 \int dy_0 \int dp_{x0} \int dp_{y0} \int dp_{z0} f_0(\psi_0, x_0, y_0, p_{x0}, p_{y0}, p_{z0}) (\dots), \quad (9)$$

and is the integral over all the various initial conditions at  $z = 0$ , where  $f_0$  is the initial electron beam distribution function and  $f_0$  is normalized such that  $\langle (1) \rangle = 1$ . For a parabolic transverse electron beam profile,  $\sigma_b = \pi(r_b^2/2)$ , and  $\kappa = \nu(c/\omega)F_B$ , where  $\nu = \omega_b^2 \sigma_b / 4\pi c^2 \simeq I(A)/17 \times 10^3$  is Budker's constant and  $r_b$  is the edge radius of the electron beam.

The radiation amplitude evolves as electrons move in the longitudinal ponderomotive potential field formed by the beating of the wiggler field and the radiation field. The electron's phase in the ponderomotive potential field is defined as  $\psi$ , where

$$\psi(z; \psi_0, x_0, y_0, p_{x0}, p_{y0}, p_{z0}) = \int_0^z \left( \frac{\omega}{c} + k_w(z') - \frac{\omega}{\bar{v}_z(z')} \right) dz' + \bar{\phi} + \psi_0, \quad (10)$$

$\psi_0$  is the initial phase in the ponderomotive potential well,  $(x_0, y_0)$  are the initial transverse positions,  $(p_{x0}, p_{y0})$  are the initial transverse momentum and  $p_{z0}$  is the initial axial momentum.

At this point in the SDE analysis, the function  $H(z)$  is arbitrary. If  $H(z)$  is not specified, the equations for  $a_{m,p}$  and  $b_{m,p}$  in (5) are underdetermined, i.e., there are more equations than unknowns. The SDE method provides a representation for  $r_s$  and  $\alpha$  that yields analytical results and minimizes the numerical computation in a fully self-consistent simulation. It is assumed that the radiation beam profile remains approximately Gaussian with a nearly circular cross section. In this case we expect the magnitude of the coefficients,  $a_{m,p}(z)$  and  $b_{m,p}(z)$  to become progressively smaller as  $m$  and  $p$  take on larger values. Hence, if the lowest order mode  $a_{0,0}$  gives a rough approximation to the radiation field, we may solve for  $a_{0,0}(z)$ ,  $r_s(z)$  and  $\alpha(z)$ . We find

$$(\partial/\partial z + Q_{0,0})a_{0,0} \simeq -iF_{0,0}, \quad (11)$$

and

$$B \simeq F_{1,0}/a_{0,0}. \quad (12)$$

Equation (12) above yields the following first order coupled differential equation for  $r_s(z)$  and  $\alpha(z)$ ,

$$r'_s - 2 \frac{c}{\omega} \frac{\alpha}{r_s} = - \frac{r_s}{a_{0,0}} (F_{1,0})_I, \quad (13a)$$

$$\alpha' - 2 \frac{c}{\omega} \frac{(1 + \alpha^2)}{r_s^2} = \frac{2}{a_{0,0}} [(F_{1,0})_R - \alpha (F_{1,0})_I], \quad (13b)$$

where  $(\ )_{R,I}$  denotes the real and imaginary parts of the enclosed function. In the SDE method, the function  $H(z)$  is specified by (13).

The particle motion in the  $z$ -direction is best written in terms of the equation for the phase  $\psi$  and the total relativistic gamma,

$$\frac{d\gamma}{dz} = - \frac{\omega/c}{\tilde{\gamma}} F_B \bar{a}_w(\tilde{x}, \tilde{y}, z) |a(\tilde{x}, \tilde{y}, z)| \sin \psi, \quad (14)$$

and

$$\frac{d(\psi - \tilde{\phi})}{dz} = -k_w(0) \frac{\omega/c(1 + \bar{a}_w(\tilde{x}, \tilde{y}, z)^2)}{\tilde{\beta}_z(1 + \tilde{\beta}_z)\tilde{\gamma}^2} + k_w(z), \quad (15)$$

where  $\beta_z = v_z/c$ .

### Description of the 3-D FEL Code SHERA

SHERA is a steady-state, single frequency code, which uses the SDE method to evaluate the radiation beam in the FEL. It incorporates realistic wiggler effects, such as transverse gradient and wiggler noise. In the results presented here, the wiggler is assumed to be free of field errors and it has weak focusing in both the  $x$  and  $y$  planes via parabolic pole pieces<sup>9</sup>, i.e.,

$$A_x(x, y, z) = A_w(z) \cosh(k_{w,x}x) \cosh(k_{w,y}y), \quad (16)$$

where  $k_{w,x}^2 + k_{w,y}^2 = k_w^2$ . For equal focusing in the  $x$  and  $y$  plane implies,  $k_{w,x} = k_{w,y}$ .

The wiggler field can be tapered by assigning a functional form for  $k_w(z)$ ,  $a_w(z)$  or resonant phase associated with a test particle. The resonant phase is defined as the phase associated with the bottom of the ponderomotive potential well,  $\psi_R = \text{constant}$ . A test particle trapped at the resonant phase satisfies the following equation

$$\frac{d^2\psi_R}{dz^2} = 0 = T(z) - \tilde{K}_s^2 \sin \psi_R, \quad (17)$$



where

$$T(z) = \frac{dk_w}{dz} - \frac{\omega/c}{2\bar{\gamma}^2} \frac{d\bar{a}_w^2}{dz},$$

and  $\bar{K}_s^2 = ((1 + \bar{a}_w^2)/\bar{\gamma}^4)(\omega/c)^2 F_B \bar{a}_w |\bar{a}|$  is the synchrotron wave number, where “-” denotes the value associated with the test particle.

For simplicity, the electron distribution function is assumed to be separable in this paper, i.e.,  $f_o = f_p(\psi_0) f_e(x_0, y_0, p_{x0}, p_{y0}) f_z(p_{z0})$ . The initial transverse electron beam distribution is assumed to have a water bag distribution, i.e., the electron density is

$$f_e = \begin{cases} 1/V & R_b < r_b, \\ 0 & R_b > r_b, \end{cases} \quad (18)$$

where  $R_b^2 = x_0^2 + y_0^2 + (v_{x0}^2 + v_{y0}^2)/(k_\beta(0)c)^2$  is the radius in the emittance space,  $V$  is the 4-dimensional phase space volume and  $\bar{k}_\beta = a_w(\bar{x}, \bar{y}, z)k_w/\bar{\gamma}$  is the betatron wave number for a parabolic pole face with equal focusing in both the  $x$  and  $y$  planes. Integrated over the transverse velocity, the electron beam has a parabolic density profile with the beam density  $n_0$  on axis where  $r_b$  is the beam edge radius.

The transverse motion of the electrons due to finite emittance in the realistic wiggler can be expressed accurately by an analytical expression for  $yk_w \ll 1$ . The particle motion is approximately,

$$\begin{bmatrix} \bar{x} \\ \bar{y} \end{bmatrix} = \left( \frac{\bar{k}_\beta(0)}{\bar{k}_\beta(z)} \right)^{1/2} \begin{bmatrix} x_0 \cos \bar{\Phi} + v_{x0} \sin \bar{\Phi} \\ y_0 \cos \bar{\Phi} + v_{y0} \sin \bar{\Phi} \end{bmatrix}, \quad (19)$$

where  $\bar{\Phi} = \int_0^z k_\beta(z') dz'$ .

In the following simulations, the electron beam is matched at the entrance of the wiggler, i.e., the electron beam radius inside the wiggler is uniform if the wiggler parameters are constant. The matching condition becomes

$$r_b = \left( \frac{\lambda_w(0)\epsilon_n}{\pi a_w} \right)^{1/2}, \quad (20)$$

where  $\lambda_w$  is the wavelength of the wiggler,  $\epsilon_n$  is the normalized beam edge emittance,  $\pi\epsilon_n/\beta\gamma$  is the electron beam area in transverse phase space.

The beam current is modeled by discrete macro particles. To minimize the number of electrons in the simulation, the integrals over the initial conditions are performed

by quadratures. Gaussian quadrature is used for the initial phase  $\psi_0$  and a 72 point quadrature<sup>10</sup> is used for the 4-dimensional transverse emittance. The energy spread is modeled by Gaussian, top-hat or any prescribed distribution functions, and implemented by either evenly spaced grids, or Gaussian quadrature. For simulations in this paper, the full interval of the Gaussian quadrature for the energy spread is 1.25 times the Gaussian width.

## RF Linac Driven Power Amplifiers

RF linacs have only been used as drivers for FEL oscillators due to low gain. Because of significant continuous advances in reducing beam emittance and increasing beam current, i.e., high beam brightness, RF linacs appear to be suitable to drive FEL amplifiers. With the improvement in electron beam brightness, the high power FEL oscillator configuration becomes less attractive, mainly because of the problem of mirror damage. In this paper we present two configurations which can achieve high gain and high efficiency. These are the master oscillator power amplifier (MOPA) and the single stage power amplifier (SSPA) configurations.

### I. Master Oscillator Power Amplifier (MOPA)

The MOPA concept, Fig. 1a, consists of trapping the electrons in the ponderomotive potential well and tapering the wiggler from the entrance to the exit of the wiggler for efficiency enhancement. To create a large ponderomotive potential well requires high power input radiation from a master oscillator. The large input laser can be an FEL oscillator. We will give an example of an RF linac that will produce  $1 \mu m$  radiation in the MOPA configuration with high efficiency and high power. The parameters of the wiggler, the input radiation and the electron beam are given in Table I.

The electron beam has an energy of  $140 \text{ MeV}$ , a peak current of  $500 \text{ A}$ , an intrinsic energy spread of  $1.0\%$  FWHM, a normalized edge emittance of  $\epsilon_n = 0.008 \text{ cm} - \text{rad}$  and a beam brightness of  $B = 1.3 \times 10^{10} \text{ A}/(\text{m} - \text{rad})^2$ . These parameters are not too different from the existing RF linac beam at Boeing Aerospace Company.

The amplitude of the vector potential of the wiggler is tapered for efficiency enhancement, see Fig. 2. The taper is slow initially and becomes faster at the end of the wiggler. If all the electrons are trapped, the maximum efficiency would be 15.8%.

The following simulation results are obtained with an injected radiation that is focused at the entrance of the wiggler with a flat wavefront. The efficiency and radiation guiding can be further improved by moving the focal point, but will not be presented here.

For an input radiation power of 50 MW, focused to a spot size of 0.1 cm, the fractional trapping potential is

$$\frac{|e|\phi_{trap}}{\gamma m_0 c^2} = 4 \left( \frac{a_w a_{00}}{1 + a_w^2} \right)^{1/2} = 1.6\%. \quad (21)$$

The estimate of the trapping potential has to be adjusted by the initial resonant phase, which is  $\sin \psi_R = 0.25$ . The actual trapping potential is sufficient for trapping an electron beam with a 1.0% energy spread. Since the radiation grows rapidly, some of the electrons not originally inside the separatrix can become recaptured.

In this illustration, an axially symmetric electron beam and radiation beam are assumed. The wiggler has parabolic pole faces so that weak transverse focusing is the same in both the x and y planes. A total of 10 Gaussian-Laguerre modes were used in the simulation. The differences in results using 10 Gaussian-Laguerre modes versus 6 Gaussian-Laguerre modes is typically much less than 5%.

Figure 3 is a plot of the radiation spot size as a function of distance. In the absence of optical guiding, the Rayleigh length would be 3 m, and at the end of the interaction the radiation spot size would be 13 times larger than the initial spot size of 0.1 cm. As a result of optical guiding, the final spot size is only 0.32 cm. The radiation is therefore able to propagate through the vacuum chamber without significant loss, because the condition  $g = 2.5 \text{ cm} > 5r_s + 0.3 \text{ cm} = 1.9 \text{ cm}$  is satisfied, where  $g$  is minimum wiggler gap<sup>11</sup>.

Figure 4 is a plot of the radiation power in each mode as a function of axial distance. The fundamental mode clearly dominates and the SDE method is extremely accurate for evaluating the spot size and wave front curvature.

Figure 5 is a plot of the efficiency as a function of beam energy spread. For electron beams with energy spread less than 1.0% Gaussian full width, the smaller input radiation power gives a higher efficiency. This is a consequence of optical guiding. We have shown

in Ref. 6 that perfectly guided radiation beams cannot be maintained in the high-gain trapped-particle regime. However, the radiation is well-focused compared to free space diffraction. The envelope equation for the radiation beam has the form<sup>6-7</sup>

$$r_s'' + K^2 r_s = 0. \quad (22)$$

The parameter governing radiation focusing is

$$K^2 = \left( \frac{2c/\omega}{r_s^2} \right)^2 \left( -1 + C^2 \langle \sin \psi \rangle^2 + 2C \langle \cos \psi \rangle + \frac{\omega}{2c} r_s^2 C' \langle \sin \psi \rangle \right), \quad (23)$$

where  $C(z) = (2\nu/\gamma)(1-f)(1+f)^{-2}(a_w/|a_{0,0}(z)|)$  is the coupling coefficient,  $f(z) = \sigma_b/\sigma_r$  is the filling factor, and  $\sigma_r = \pi r_s^2$  is the area of the radiation beam. The first term on the right-hand side of (23) is defocusing and corresponds to the usual diffraction expansion, the second and third terms are always focusing while the last term is usually a defocusing contribution. For perfectly guided beams,  $K^2 = 0$ . For weakly guided beams, the focusing terms are reduced. The coupling coefficient  $C$  is larger when the initial input is smaller. Thus, the radiation focuses better when the input power is smaller. Figure 6 is a comparison of radiation spot sizes as a function of  $z$  for the input radiations of (—) 50 MW and (---) 500MW obtained for simulations with no energy spread. The spot size associated with 50 MW input is smaller and the final efficiency is larger.

## II. Single Stage Power Amplifier (SSPA)

A somewhat simpler configuration, that can achieve high power and high efficiency, is the single stage power amplifier (SSPA)<sup>12</sup>. In the SSPA configuration (see Fig. 1b), a low power laser, such as a dye laser, is directly amplified and optically guided in a uniform wiggler region until saturation occurs. The intrinsic efficiency in the uniform wiggler region is small, typically less than 2%. For efficiency enhancement, the wiggler is spatially tapered just prior to saturation. At this point the electron beam is tightly bunched in the ponderomotive wave, and the trapping potential can be sufficiently large. The SSPA configuration requires a slightly longer overall wiggler length. The main advantage of the SSPA configuration is the elimination of the high power master oscillator.

The parameters of the wiggler, the input radiation and the electron beam for the 1  $\mu\text{m}$  SSPA configuration are given in Table II. The electron beam has an energy of 250 MeV, a peak current of 1 kA, an intrinsic energy spread of 1.0% FWHM, a normalized edge emittance of  $\epsilon_n = 0.007 \text{ cm rad}$  and thus, a beam brightness  $B = 5 \times 10^{11} \text{ A/(m - rad)}^2$ .

The following simulation results are obtained with an injected radiation beam power of 15 kW peak, focused at the entrance of the wiggler to a spot size of 0.11 cm. The free space Rayleigh length is 4 m. At exact resonance, the radiation saturates at a distance of 15 m with an intrinsic efficiency of 0.39%. At the end of the uniform wiggler region, the trapping potential is

$$\frac{|e|\phi_{\text{trap}}}{\gamma m_0 c^2} = 4 \left( \frac{a_w a_{00}}{1 + a_w^2} \right)^{1/2} = 3.2\%.$$

In the uniform wiggler section, the radiation beam is optically guided and the magnetic field amplitude and period are 3.155 kG and 9.6 cm, respectively. The wiggler taper begins just prior to the saturation point ( $z = 15 \text{ m}$ ). Figure 7 shows the taper of the amplitude of the vector potential of the wiggler. If all the electrons are trapped, the maximum efficiency would be 27%. A plot of the efficiency as a function of the axial distance is shown in Fig. 8. The maximum efficiency is 22% at the end of the wiggler and a substantial fraction of the beam electrons are trapped in the ponderomotive buckets. Figure 9 indicates that the wiggler can be tapered further to obtain even higher efficiencies. The spot size of the radiation field is plotted in Fig. 9. The spot size at the end of the wiggler is 0.24 cm.

### Conclusions

With the recent advances in RF linac technology towards higher power and higher brightness, FEL configurations driven by RF linacs are no longer limited to oscillators. We have presented examples of the MOPA and SSPA configurations for achieving high FEL power and efficiency. The SSPA is the simpler of the two configurations because the high power master oscillator is replaced with a low power conventional laser source.

### Acknowledgments

This work has been supported by ONR.

## References

- [1] P. Sprangle and C. M. Tang, Appl. Phys. Lett. 39, 677 (1981); AIAA J. 19, 1164 (1981); C. M. Tang and P. Sprangle, *Free-Electron Generator of Coherent Radiation*, Physics of Quantum Electronics, Vol. 9, eds., S. F. Jacobs, G. T. Moore, H. S. Pilloff, M. Sargent III, M. O. Scully, R. Spitzer (Edison-Wesley, Reading, MA, 1982) p. 627.
- [2] G. T. Moore, Opt. Comm. 52, 46(1984), 54, 121 (1985).
- [3] G. T. Moore, Nucl. Instr. and Methods in Phys. Res. 239, 19 (1985).
- [4] E. T. Scharlemann, A. M. Sessler and J. S. Wurtele, Phys. Rev. Lett. 54, 1925 (1985).
- [5] M. Xie and D. A. G. Deacon, Nucl. Instr. and Methods in Phys. Res. A250, 426 (1986).
- [6] P. Sprangle, A. Ting and C. M. Tang, Phys. Rev. Lett. 59, 202 (1987); P. Sprangle, A. Ting and C. M. Tang, Phys. Rev. A30, 2773 (1987).
- [7] P. Sprangle, A. Ting, B. Hafizi and C. M. Tang, Nucl. Instr. and Methods in Phys. Res. A272, 536, 1988.
- [8] C. M. Tang and P. Sprangle, IEEE J. Quantum Electron., QE-21, 970(1985).
- [9] E. T. Scharlemann, J. Appl. Phys., 58, 2154(1985).
- [10] A. H. Stroud, *Approximate Calculation of Multiple Integrals*, Prentice-Hall, Inc., Englewood Cliffs, NJ, 1971, p. 293.
- [11] K. Halbach, Journal De Physique, Colloque C1, supplement au n°2, Tome 44, 211 (1983).
- [12] Private communications with L. Thode at LANL and D. Prosnitz at LLNL.

Table I

Parameters of Numerical Simulation in the MOPA ConfigurationElectron Beam (parabolic density profile)

Energy, $E$	140 MeV
Current, $I$	500 A
Intrinsic E-spread, $\Delta E/E$	1.0% (Gaussian full width)
Slippage distance	0.08 cm
Norm. edge emittance, $\epsilon_n$	0.008 cm-rad
Radius, $r_b$	0.08 cm
Energy spread due to $\epsilon_n$ , $\frac{\Delta\gamma_e}{\gamma_e} = \frac{1}{2} \frac{\epsilon_n^2}{r_b^2} \frac{1}{1+a_w^2}$	0.17%

Wiggler (linearly polarized)

Period, $\lambda_w$	5.0 cm
Init. magnetic field, $B_w$	4.28 kG
Final magnetic field, $B_w$	3.21 kG
Wiggler length, $L_w$	40 m
Initial normalized vector potential, $a_w$	$\sqrt{2}$
Taper (amplitude)	non-uniform (max 15.8%)

Radiation

Wavelength, $\lambda$	1 $\mu m$
Input power, $P_{in}$	50 MW
Min. spot size of input rad.	0.1 cm (at $z = 0$ m)
Initial Rayleigh length	3.0 m
Final spot size, $r_s$ ( $z=40$ m)	0.32 cm
Output power, $P_{out}$ (peak)	5.2 GW
Efficiency at end of wiggler	7.5%

Table II

Parameters of Numerical Simulation in the Power Amplifier ConfigurationElectron Beam (parabolic density profile)

Energy, $E$	250 MeV
Current, $I$	1000 A
Intrinsic E-spread, $\Delta E/E$	1.0% (Gaussian full width)
Slippage distance	0.08 cm
Norm. edge emittance, $\epsilon_n$	0.007 cm-rad
Radius, $r_b$	0.087 cm
Energy spread due to $\epsilon_n$ , $\frac{\Delta\gamma_e}{\gamma_e} = \frac{1}{2} \frac{\epsilon_n^2}{r_b^2} \frac{1}{1+a_w^2}$	0.06%

Wiggler (linearly polarized)


Period, $\lambda_w$	9.6 cm
Init. magnetic field, $B_w$	3.155 kG
Final magnetic field, $B_w$	2.05 kG
Wiggler length, $L_w$	80 m
Initial normalized vector potential, $a_w$	2.0
Taper (amplitude)	non-uniform (max 27%)

Radiation

Wavelength, $\lambda$	1 $\mu m$
Input power, $P_{in}$	15 kW
Min. spot size of input rad.	0.11 cm (at $z = 0$ m)
Initial Rayleigh length	4.0 m
Final spot size, $r_s$ ( $z=80$ m)	0.23 cm
Output power, $P_{out}$ (peak)	53 GW
Efficiency at end of wiggler	22%



### (a) Master Oscillator Power Amplifier (MOPA)



### (b) Single Stage Power Amplifier (SSPA)




Fig. 1. Schematic diagram of (a) the master oscillator power amplifier (MOPA) configuration and (b) the single stage power amplifier (SSPA) configuration.




Fig. 2. Plot of the amplitude of the normalized vector potential of the wiggler as function of interaction distance  $z$ .




Fig. 3. Plot of the radiation spot size as a function of distance  $z$  for 1.0% Gaussian full width energy spread.




Fig. 4. Plot of radiation power for each mode as a function of distance with initial radiation input power of 50 MW.




Fig. 5. Plot of the Efficiency as a function of energy spread for input radiation power of (—) 50 MW and (---) 500 MW.




Fig. 6. Plots of spot sizes as a function of axial distance for an electron beam with no initial energy spread for input radiation power of (—) 50 MW and (--) 500 MW.




Fig. 7. Plot of the amplitude of the normalized vector potential of the wiggler as a function of interaction distance  $z$ .




Fig. 8. Plot of the radiation spot size as a function of distance  $z$  for 1.0% Gaussian full width energy spread.






Fig. 9. Plot of efficiency as a function of the axial distance  $z$ .

# DISTRIBUTION LIST

Naval Research Laboratory  
4555 Overlook Avenue, S.W.  
Washington, DC 20375-5000

Attn: Code 1000 - Commanding Officer, CAPT John J. Donegan, Jr.  
1001 - Dr. T. Coffey  
1005 - Head, Office of Management & Admin.  
1005.1-Deputy Head, Office of Management & Admin.  
1005.6-Head, Directives Staff  
1200 - CAPT R. W. Michaux  
1201 - Deputy Head, Command Support Division  
1220 - Mr. M. Ferguson  
2000 - Director of Technical Services  
2604 - NRL Historian  
3000 - Director of Business Operations  
4000 - Dr. W. R. Ellis  
0124 - ONR  
4600 - Dr. D. Nagel  
4603 - Dr. W. W. Zachary  
4700 - Dr. S. Ossakow (26 copies)  
4700.1-Dr A. W. Ali  
4790 - Dr. P. Sprangle (25 copies)  
4790 - Dr. C. A. Kapetanakis  
4790 - Dr. J. Mathew  
4730 - Dr. R. Elton  
4707 - Dr. W. M. Manheimer  
4790 - Dr. W. Black  
4790 - Dr. A. W. Fliflet  
4790 - Dr. S. Gold  
4790 - Dr. D. L. Hardesty  
4790 - Dr. A. K. Kinhead  
4790 - Dr. M. Rhinevine  
4770 - Dr. G. Cooperstein  
4790 - Dr. C. M. Tang (25 copies)  
4790 - Dr. G. Joyce  
4790 - Dr. M. Lampe  
4790 - Dr. Y. Y. Lau  
4790 - Dr. A. Ting (25 copies)  
4790 - Dr. E. Esarey  
4790 - Dr. J. Krall  
4790A- B. Pitcher (25 copies)  
5700 - Dr. L. A. Cosby  
5745 - Dr. J. Condon  
6840 - Dr. S. Y. Ahn  
6840 - Dr. A. Ganguly  
6840 - Dr. R. K. Parker  
6843 - Dr. R. H. Jackson  
6843 - Dr. N. R. Vanderplaats  
6843 - Dr. C. M. Armstrong  
6875 - Dr. R. Wagner  
2628 - Documents (22 copies)  
2634 - D. Wilbanks

NOTE: Every name listed on distribution gets one copy except for those where extra copies are noted.

Dr. R. E. Aamodt  
Lodestar Research Corp.  
2400 Central Ave., P-5  
Boulder, CO 80306-4545

Dr. J. Adamski  
Boeing Aerospace Company  
P.O. Box 3999  
Seattle, WA 98124

Dr. T. M. Antonsen  
University of Maryland  
College Park, MD 20742

Assistant Secretary of the  
Air Force (RD&L)  
Room 4E856, The Pentagon  
Washington, D.C. 20330

Dr. W. A. Barletta  
Lawrence Livermore National Lab.  
P. O. Box 808  
Livermore, CA 94550

Dr. W. Becker  
Univ. of New Mexico  
Institute for Mod. Opt.  
Albuquerque, NM 87131

Dr. Robert Behringer  
9342 Balcon Ave.  
Northridge, CA 91325

Dr. G. Bekefi  
Mass. Institute of Tech.  
Room 36-213  
Cambridge, MA 02139

Dr. Steven V. Benson  
Physics Building  
Duke University  
Durham, NC 27706

Dr. I. B. Bernstein  
Mason Laboratory  
Yale University  
400 Temple Street  
New Haven, CT 06520

Dr. Amitava Bhattacharjee  
Columbia University  
S. W. Mudd 210  
Dept. of Applied Phys.  
New York, NY 10027

Dr. Anup Bhowmik  
Rockwell International/Rocketdyne Div.  
6633 Canoga Avenue, FA-40  
Canoga Park, CA 91304

Dr. G. Bourianoff  
1901 Rutland Drive  
Austin, TX 78758

Dr. Charles Brau  
Vanderbilt University  
Nashville, TN 37235

Dr. R. Briggs  
SSC Laboratory  
Stoneridge Office Park  
2550 Beckleymeade Ave.  
Suite 260  
Dallas, TX 75237

Prof. William Case  
Dept. of Physics  
Grinnell College  
Grinnell, IA 50112

Dr. R. Center  
Spectra Tech., Inc.  
2755 Northup Way  
Bellevue, WA 98004

Dr. K. C. Chan  
Los Alamos National Laboratory  
P. O. Box 1663  
Los Alamos, NM 87545

Prof. Frank Chen  
School of Eng. & Applied Sciences  
Univ. of Calif. at Los Angeles  
7731 K Boelter Hall  
Los Angeles, CA 90024

Dr. S. Chen  
MIT Plasma Fusion Center  
NW16-176  
Cambridge, MA 01890

Dr. D. P. Chernin  
Science Applications Intl. Corp.  
1720 Goodridge Drive  
McLean, VA 22102

Dr. William Colson  
Berkeley Research Assoc.  
P. O. Box 241  
Berkeley, CA 94701

Dr. Richard Cooper  
Los Alamos National Scientific  
Laboratory  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. R. A. Cover  
Rockwell International/Rocketdyne Div.  
6633 Canoga Avenue, FA-38  
Canoga Park, CA 91304

Dr. Bruce Danly  
MIT  
NW16-174  
Cambridge, MA 02139

Dr. R. Davidson  
Plasma Fusion Center  
Mass. Institute of Tech.  
Cambridge, MA 02139

Dr. John Dawson  
Physics Department  
University of California  
Los Angeles, CA 90024

Dr. David A. G. Deacon  
Deacon Research  
Suite 203  
900 Welch Road  
Palo Alto, CA 94304

Dr. Philip Debenham  
Center for Radiation Research  
National Bureau of Standards  
Gaithersburg, MD 20899

Director  
National Security Agency  
Fort Meade, MD 20755  
ATTN: Dr. Richard Foss, A42  
Dr. Thomas Handel, A243  
Dr. Robert Madden, R/SA

Director of Research (2 copies)  
U. S. Naval Academy  
Annapolis, MD 21402

Dr. A. Drobot  
Science Applications Intl. Corp.  
1710 Goodridge Road  
McLean, VA 22102

Dr. Dwight Duston  
SDIO/IST  
The Pentagon  
Washington, DC 20301-7100

Dr. J. A. Edighofer  
TRW, Bldg. R-1  
One Space Park  
Redondo Beach, CA 90278

Dr. Luis R. Elias  
Creol-FEL Research Pavillion  
Suite 400  
12424 Research Parkway  
Orlando, FL 32826

Dr. C. James Elliott  
X1-Division, M.S. 531  
Los Alamos Natl. Scientific Lab.  
P. O. Box 1663  
Los Alamos, NM 87545

Dr. Anne-Marie Fauchet  
Brookhaven National Laboratories  
Associated Universities, Inc.  
Upton, L.I., NY 11973

Dr. R. Gajewski  
Div. of Advanced Energy Projects  
U. S. Dept of Energy  
Washington, DC 20545

Dr. J. Gallardo  
Brookhaven National Laboratory  
Associated Universities, Inc.  
Upton, L.I., NY 11973

Dr. B. B. Godfrey,  
Chief Scientist  
WL/CA  
Kirtland AFB, NM 87117-6008

Dr. John C. Goldstein, X-1  
Los Alamos Natl. Scientific Lab.  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. V. L. Granatstein  
Dept. of Electrical Engineering  
University of Maryland  
College Park, MD 20742

Dr. K. Halbach  
Lawrence Berkeley Laboratory  
University of California, Berkeley  
Berkeley, CA 94720

Dr. R. Harvey  
Hughes Research Laboratory  
3011 Malibu Canyon Road  
Malibu, CA 90265

Prof. Herman A Haus  
Mass. Institute of Technology  
Rm. 36-351  
Cambridge, MA 02139

Dr. B. Hui  
Defense Advanced Research Projects Agency  
1400 Wilson Blvd.  
Arlington, VA 22209

Prof. V. Jaccarino  
Univ. of Calif. at Santa Barbara  
Santa Barbara, CA 93106

Dr. B. Carol Johnson  
Ctr. for Radiation Research  
National Inst. of Standards and Tech.  
Gaithersburg, MD 20899

Dr. Ron Johnson  
Ctr. for Radiation Research  
Natl. Inst. of Standards and Tech.  
Gaithersburg, MD 20899

Dr. Shayne Johnston  
Physics Department  
Jackson State University  
Jackson, MS 39217

Dr. R. A. Jong  
Lawrence Livermore National Laboratory  
P. O. Box 808/L626  
Livermore, CA 94550

Dr. Howard Jory  
Varian Associates, Bldg. 1  
611 Hansen Way  
Palo Alto, CA 94303

Dr. C. Joshi  
University of California  
Los Angeles, CA 90024

Dr. K. J. Kim, MS-101  
Lawrence Berkeley Lab.  
Rm. 223, B-80  
Berkeley, CA 94720

Dr. Brian Kincaid  
Lawrence Berkeley Laboratory  
University of California, Berkeley  
Berkeley, CA 94720

Prof. N. M. Kroll  
Department of Physics  
B-019, UCSD  
La Jolla, CA 92093

Dr. Thomas Kwan  
Los Alamos National Scientific  
Laboratory, MS608  
P. O. Box 1663  
Los Alamos, NM 87545

Dr. J. LaSala  
Physics Dept.  
U. S. M. A.  
West Point, NY 10996

Dr. Michael Lavan  
U.S. Army Strategic Def. Command  
ATTN: Code CSSD-H-D  
P. O. Box 1500  
Huntsville, AL 35807-3801

Dr. B. Levush  
Dept. of Physics & Astronomy  
University of Maryland  
College Park, MD 20742

Dr. Anthony T. Lin  
Dept. of Physics  
University of California  
Los Angeles, CA 90024

Dr. Chuan S. Liu  
Dept. of Physics & Astronomy  
University of Maryland  
College Park, MD 20742

Dr. A. Luccio  
Brookhaven National Laboratory  
Accelerator Dept.  
Upton, NY 11973

Prof. J.M.J. Madey  
117 Physics Bldg.  
Duke University  
Durham, NC 27706

Dr. R. Mako  
205 South Whiting Street  
Alexandria, VA 22304

Dr. Joseph Mangano  
Science Research Laboratory  
1600 Wilson Blvd.  
Suite 1200  
Arlington, VA 22209

Dr. Siva A. Mani  
Science Applications Intl. Corp.  
1040 Waltham Street  
Lexington, MA 02173-8027

Dr. T. C. Marshall  
Applied Physics Department  
Columbia University  
New York, NY 10027

Dr. Xavier K. Maruyama  
Dept. of Physics  
Naval Postgraduate School  
Monterey, CA 93943

Dr. B. McVey  
Los Alamos National Laboratory  
P. O. Box 1663  
Los Alamos, NM 87545

Dr. David Merritt  
Space & Naval Warfare Command  
Attn: PMW 145A  
Washington, DC 20363-5100

Dr. A. Mondelli  
Science Applications Intl. Corp.  
1710 Goodridge Drive  
P.O. Box 1303  
McLean, VA 22101

Dr. Mel Month  
Brookhaven National Laboratories  
Associated Universities, Inc.  
Upton, L.I., NY 11973

Dr. Gerald T. Moore  
University of New Mexico  
Albuquerque, NM 87131

Dr. Philip Morton  
Stanford Linear Accelerator Center  
P.O. Box 4349  
Stanford, CA 94305

Prof. J. Nation  
224 Phillips Hall  
School of Elec. Eng.  
Cornell University  
Ithaca, NY 14850

Dr. George Neil  
TRW  
One Space Park  
Redondo Beach, CA 90278

Dr. Kelvin Neil  
Lawrence Livermore National Lab.  
Code L-321, P.O. Box 808  
Livermore, CA 94550

Dr. Brian Newnam  
MSJ 564  
Los Alamos National Scientific Lab.  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. T. Orzechowski  
L-436  
Lawrence Livermore National Lab.  
P. O. Box 808  
Livermore, CA 94550

Prof. E. Ott  
Department of Physics  
University of Maryland  
College Park, MD 20742

OUSDRE (R&AT)  
Room 3D1067, The Pentagon  
Washington, D.C. 20301

Dr. Robert B. Palmer  
Brookhaven National Laboratories  
Associated Universities, Inc.  
Upton, L.I., NY 11973

Dr. J. Palmer  
Hughes Research Laboratory  
Malibu, CA 90265

Dr. Richard H. Pantell  
Stanford University  
Stanford, CA 94305

Dr. Dennis Papadopoulos  
Astronomy Department  
University of Maryland  
College Park, Md. 20742

Dr. John A. Pasour  
Mission Research Laboratory  
8560 Cinderbed Road  
Suite 700  
Newington, VA 22122

Dr. C. K. N. Patel  
Bell Laboratories  
Murray Hill, NJ 07974

Dr. Claudio Pellegrini  
Brookhaven National Laboratory  
Associated Universities, Inc.  
Upton, L.I., NY 11973

Dr. S. Penner  
Center for Radiation Research  
Natl. Inst. of Standards and Tech.  
Gaithersburg, MD 20899

Dr. M. Piestrup  
Adelphi Technology  
13800 Skyline Blvd. No. 2  
Woodside, CA 94062

Dr. D. J. Pistoresi  
Boeing Aerospace Company  
P. O. Box 3999  
Seattle, WA 98124-2499

Major E. W. Pogue  
SDIO  
The Pentagon, T-DE Rm. 1E180  
Washington, DC 20301-7100

Major Donald Ponikvar  
U. S. Army SDC  
P. O. Box 15280  
Arlington, VA 22245-0280

Dr. Donald Prosnitz  
Lawrence Livermore National Lab.  
Box 5511 L-626  
Livermore, CA 94550

Dr. D. C. Quimby  
Spectra Technology  
2755 Northup Way  
Bellevue, WA 98004

Dr. G. Ramian  
Quantum Institute  
University of California  
Santa Barbara, CA 93106

Dr. M. Reiser  
University of Maryland  
Department of Physics  
College Park, MD 20742

Dr. S. Ride  
Arms Control  
Stanford University  
Stanford, CA 94305

Dr. C. W. Roberson  
Office of Naval Research  
Code 1125  
800 N. Quincy Street  
Arlington, VA 22217

Dr. K. Robinson  
Spectra Technology  
2755 Northup Way  
Bellevue, WA 98004

Dr. Marshall N. Rosenbluth  
Dept. of Physics  
B-019  
Univ. of Calif., San Diego  
LaJolla, CA 92093

Dr. J. B. Rosenzweig  
The Inst. for Accelerator Physics  
Department of Physics  
University of Wisconsin-Madison  
Madison, WI 53706

Dr. N. Rostoker  
Department of Physics  
University of California at Irvine  
Irvine, CA 92717

Dr. A. Saxman  
Los Alamos National Scientific Lab.  
P. O. Box 1663, MSE523  
Los Alamos, NM 87545

Dr. E. T. Scharlemann  
L626  
Lawrence Livermore National Laboratory  
P. O. Box 808  
Livermore, CA 94550

Prof. S. P. Schlesinger  
Dept. of Electrical Engineering  
Columbia University  
New York, NY 10027

Dr. Howard Schlossberg  
AFOSR  
Bolling AFB  
Washington, D.C. 20332

Dr. George Schmidt  
Stevens Institute of Technology  
Physics Department  
Hoboken, NJ 07030

Dr. M. J. Schmitt  
Los Alamos National Laboratory  
P. O. Box 1663  
Los Alamos, NM 87545

Dr. H. Schwettmann  
Phys. Dept. & High Energy  
Physics Laboratory  
Stanford University  
Stanford, CA 94305

Dr. Marlan O. Scully  
Dept. of Physics & Astronomy  
Univ. of New Mexico  
800 Yale Blvd. NE  
Albuquerque, NM 87131

Dr. S. B. Segall  
KMS Fusion  
3941 Research Park Dr.  
P.O. Box 1567  
Ann Arbor, MI 48106

Prof. P. Serafim  
Northeastern University  
Boston, MA 02115

Dr. A. M. Sessler  
Lawrence Berkeley Laboratory  
University of California  
1 Cyclotron Road  
Berkeley, CA 94720

Dr. W. Sharp  
L-626  
Lawrence Livermore National Laboratory  
P. O. Box 808  
Livermore, CA 94550

Dr. Earl D. Shaw  
Bell Laboratories  
600 Mountain Avenue  
Murray Hill, NJ 07974

Dr. R. L. Sheffield  
Los Alamos National Laboratory  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. D. Shoffstall  
Boeing Aerospace Company  
P.O. Box 3999  
Seattle, WA 98124

Dr. Jack Slater  
Spectra Technology  
2755 Northup Way  
Bellevue, WA 98004

Dr. Todd Smith  
Hansen Labs  
Stanford University  
Stanford, CA 94305

Dr. R. Sudan  
Lab. of Plasma Studies  
Cornell University  
Ithaca, NY 14850

Dr. David F. Sutter  
ER 224, GTN  
Department of Energy  
Washington, D.C. 20545

Dr. T. Tajima  
Institute for Fusion Studies  
University of Texas at Austin  
Austin, TX 78712

Dr. R. Temkin  
Mass. Institute of Technology  
Plasma Fusion Center  
Cambridge, MA 02139

Dr. L. Thode  
Los Alamos National Laboratory  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. Norman E. Tolk  
Physics Department  
Vanderbilt University  
Nashville, TN 37240

Dr. Kang Tsang  
Science Applications Intl. Corp.  
1710 Goodridge Dr.  
McLean, VA 22102



Dr. H. S. Uhm  
Naval Surface Warfare Center  
White Oak Lab.  
Silver Spring, MD 20903-5000

Under Secretary of Defense (R&D)  
Office of the Secretary of Defense  
Room 3E1006, The Pentagon  
Washington, D.C. 20301

Dr. John E. Walsh  
Wilder Laboratory  
Department of Physics (HB 6127)  
Dartmouth College  
Hanover NH 03755

Dr. Jiunn-Ming Wang  
Brookhaven National Laboratories  
Associated Universities, Inc.  
Upton, L.I., NY 11973

Dr. Roger W. Warren  
Los Alamos National Scientific Lab.  
P.O. Box 1663  
Los Alamos, NM 87545

Dr. J. Watson  
Los Alamos National Laboratory  
P. O. Box 1663  
Los Alamos, NM 87545

Dr. Mark Wilson  
Natl. Inst. of Standards and Tech.  
Bldg. 245, Rm. B-119  
Gaithersburg, MD 20899

Dr. J. Wurtele  
M.I.T.  
NW 16-234  
Plasma Fusion Center  
Cambridge, MA 02139

Dr. Ming Xie  
Dept. of Physics  
Stanford University  
Stanford, CA 94305

Dr. Yi-Ton Yan  
Stanford Linear Accelerator Center  
P. O. 4349  
Stanford, CA 94305

Dr. Simon S. Yu  
Lawrence Livermore National Laboratory  
P. O. Box 808  
Livermore, CA 94550

Do NOT make labels  
for these two-below:  
Records---(1 copy)

Naval Research Laboratory  
Washington, DC 20375-5000  
Code 2630  
Timothy Calderwood